






PureChill-901






Integrated Filter Monitor



ProTekk Auto-Safety Shut-off valve

Standard Features

- PureChill™ Technology
- Closed system keeps environmental contaminants out
- · Low Height (only 16 1/2") fits under standard cabinets
- · Capacitve touch dispense button for ease and durability
- Integrated Filter Monitor ensures freshly filtered water
- ProTekk[™] Auto Safety-Shut-Off Valve provides peace of mind
- Cold: 37-50° F, Adjustable Hot: 180° F, Autocontrol
- LED indicator for Hot and Cold water on the front panel
- Tall 10" fill opening allows larger cups, mugs or reusable bottles
- Easy to clean control panel
- Individual on/off control switches for cold and hot water on rear panel
- Built-in Standard Dual-Cartridge filtration system is easily accessed for replacement
- Attractive LED lighted dispense area
- · Award winning design
- 1 year limited warranty
- 3 year compressor warranty



Dimensions (inches)

Specifications

Shipping Weight: 50 lb.
Dimension: 13"W x 16"D x 16.5"H
Cooling Rate: 2.8 gal/hr 37-50 °F
Hot tank volume .5 gal
Heating Rate: 1.3 gal/hr 180 °F
Voltage: 115 VAC

Power Required: 600w max

Filter System

Standard Filter *901F*Stage 1: 5 micron Sediment

Stage 2: 10 micron Activated Carbon

Automatic tank full control Fully assembled

ADA compliant

ORDERING

3-Temp Countertop with Standard Filtration
3-Temp Countertop

3-Temp Countertop with UV sterilizer

Replacement Filters

Sediment

PWC-901F

PWC-901

add/UV

TF-4113

Carbon TF-4115





